

Zirkon® Gas CL₂

Kuntze Gas Sensors are amperometric sensors for the detection of chlorine gas.

The matching fitting Ne GSH allows for an easy installation of the gas sensor.

Advantages

- > Short response times
- > High reliability
- > Simple start-up due to printed calibration value

Zirkon® Gas CL₂



Article No.: 29111001K

Measurement Parameter

- > Chlorine gas: 0.. 20 ppm

Process conditions

- > Temperature: -20 +50 °C
- > Humidity: 15.. 90 % rH (non condensating)
- > Storage Life: 6 months in container at +4..10 °C
- > Influence of Humidity:
No effect on the zero point

Cross Sensitivity chlorine gas sensor at 20 °C

Gas	Concentration	Value Read
Bromide	10 ppm	2,5
Chlorine Dioxide	3 ppm	~3
Carbon Monoxide	300 ppm	0
Sulfure Dioxide	5 ppm	0
Nitrogen Monoxide	35 ppm	0
Hydrogen	300 ppm	0
Nitrogen Dioxide	20 ppm	~20
Hydrogen Sulfide (H ₂ S) *		ND*

* Contact with H₂S poisons the sensor, subsequent contact with chlorine reactivates it.

The influencing factor can vary from sensor to sensor and over the life span of the individual sensor. No claim to completeness of the data, the sensors can potentially exhibit cross sensitivity to other gases.



Kuntze Instruments GmbH

Robert-Bosch-Str. 7a
40688 Meerbusch
Germany

+49 2150 70660
info@kuntze.com
www.kuntze.com